

(19) World Intellectual Property Organization
International Bureau



1 1000 000000 11 00000 0000 0000 11 0000 0000 0000 0000 0000 0000 0000 0000

(43) International Publication Date
7 December 2000 (07.12.2000)


PCT

(10) International Publication Number
WO 00/73676 A1

- (51) International Patent Classification⁷: F16F 9/05, Mark, Guy [US/US]; 2203 East Arndale Road, Stow, OH 44224 (US).
B60G 11/28
- (21) International Application Number: PCT/US99/11772 (74) Agent: KRAWCZYK, Nancy, T.; D/823, The Goodyear Tire & Rubber Company, 1144 East Market Street, Akron, OH 44316-0001 (US).
- (22) International Filing Date: 28 May 1999 (28.05.1999)
- (25) Filing Language: English (81) Designated States (national): AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (26) Publication Language: English (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
- (71) Applicant (for all designated States except US): THE GOODYEAR TIRE & RUBBER COMPANY [US/US]; D/823, 1144 East Market Street, Akron, OH 44316-0001 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): TROWBRIDGE,

[Continued on next page]

(54) Title: AIR SPRING UPPER RETAINER



(57) Abstract: An air spring (1) has a cylindrical flexible airsleeve (2) secured at each end to form a fluid chamber (14). One end (6) of the sleeve (2) is secured to a retainer (8). The retainer (8) has a ribbed reinforcement structure (16) which allows the air spring (1) to be directly mounted to a moveable part of a vehicle or other machinery. The retainer (8) has an extending mounting means (13) on one side of the reinforcement structure (16) and a bead seating surface (12) adjacent to the reinforcement structure (16).

WO 00/73676 A1